

Description		FARMTRAC COMPACT RANGE			
Model Name		FT 20	FT22	FT26	FT26HST
Engine	Model	Mitsubishi MVL3 inline	Mitsubishi MVL3 inline	Mitsubishi MV S3L2 inline	Mitsubishi MV S3L2 inline
	No. of Cylinders	3	3	3	3
	Gross Output	18 HP @ 2700 RPM	21.3 HP @ 3000 RPM	24.4 HP @ 2500 RPM	24.4 HP @ 2500 RPM
	Displacement (cc)	952	952	1318	1318
	Rated RPM	2700	3000	2500	2500
	Fuel Tank Capacity	24	24	24	24
	Air Cleaner	Dry Type	Dry Type	Dry Type	Dry Type
	Lights	Projector	Projector	Projector	Projector
Transmission	Gear	9F+3R	9F+3R	9F+3R	HST 3 Range
	Type	Constant mesh	Constant mesh	Constant mesh	Constant mesh
Rear Axle	Type	Bull gear reduction	Bull gear reduction	Bull gear reduction	Bull gear reduction
	Differential Lock	Foot operated	Foot operated	Foot operated	Foot operated
Clutch type		Single Clutch	Single Clutch	Single Clutch	Not Applicable
Brake type		OIB	OIB	OIB	OIB
Speed	Forward (km/h) Max./Min	18.2/1.1	20.2/1.3	18.2/1.1	Low Range Forward: 0-6.4 Medium Range Forward: 0-9.6 High Range Forward: 0-19.1
	Reverse (km/h)	8.4/1.3	9.3/1.5	8.3/1.3	Low Range Reverse: 0-5.5 Medium Range Reverse: 0-8.2 High Range Reverse: 0-16.3
Max speed @ fly up		20.02	22.02	19.64	20.63
PTO	Speed (rpm)	540 @ 2504 /540E @ 2035 ERPM	540 @ 2504 /540E @ 2035 ERPM	540 @ 2504 /540E @ 2035 ERPM	540 @ 2504 /2283 Mid-PTO @ 2500 ERPM
	Output (HP)	14	16	18	18
	Type	Dual PTO	Dual PTO	Dual PTO	Mid- PTO
3-Point hitch		CAT 1 N	CAT 1 N	CAT 1 N	CAT 1 N
Steering	Type	Power Steering	Power Steering	Power Steering	Power Steering
	Pump Capacity (LPM)	14.5(Lift and Steering common)	14.5(Lift and Steering common)	14	14
Hydraulics	Control system	Position & Draft control	Position & Draft control	Position & Draft control	Position control
	Lift Capacity	800kg	800kg	800kg	800kg
	Hydraulic pump Capacity (LPM)	14.5(Lift and Steering common)	14.5(Lift and Steering common)	19.3	19.3
	Standard auxiliary valve	1 SA covertable to 1 DA with detent	1 SA covertable to 1 DA with detent	1 SA covertable to 1 DA with detent	1 SA covertable to 1 DA with detent
Tyre	Tyre option	Agri/Industrial/Turf	Agri/Industrial/Turf	Agri/Industrial/Turf	Agri/Industrial/Turf
	Front standard tyre (Agri)	5x12	5x12	6x12	6x12
	Rear standard tyre (Agri)	8x18 (Agri.)	8x18 (Agri.)	8.3x20 (Agri.)	8.3x20 (Agri.)
Dimension	Overall length (mm)	2674	2674	2677	2677
	Overall width (mm)	1041	1041	1041	1041
	Overall height (mm)	2162	2162	2192	2192
	Wheel base (mm)	1420	1420	1551	1551
	Ground clearance (mm)	296	296	324	324
	Front track width (mm)	835	835	838	838
	Rear track width (mm)	715-935	715-935	711-914	711-914
	Turning radius w/o brake(m)	2.5	2.5	2.6	2.6
Tractor weight (kg)	904	904	1020	1010	